



Acts as the nerve center of a modular gas detection network by providing continuous monitoring of up to 96 sensors

Manning AirAlert™ 96d multi-channel gas monitoring system



The Manning AirAlert™ 96d can support up to 96 sensors and relay modules and provides unique at-a-glance system status and can be maintained with ease using the menu driven push button controls.

This easy to use system can be completely customized in an industrial or commercial application by using any combination of Honeywell Analytics sensors. The Manning AirAlert™ 96d has the potential to complete plant control systems by operating independently, interfacing with it to create a reliable stand-alone safety system.



The Manning AirAlert™ 96d multi-channel gas monitoring system is designed for installation and operational simplicity for continuous monitoring and control of toxic gases, combustible gases and oxygen hazards.

96 Sensor Capacity

- Supports up to 96 network devices
- Three distinct channels act as the nerve centre of a modular gas detection network

Menu-Driven Program

- Easily fine-tune applications ranging from minor operational sequences to reconfiguration of entire network
- Simple push-button program facilitates adjustments

Customizable

- Supports any combination of Honeywell Analytics gas sensors, including NH₃, CO₂, H₂, CO, Cl₂, CFC's, HCFC's, HFC's, CH₄, O₂, NO₂, and more
- Field-programmable alarm levels for each sensor
- Zoning capability allows for up to 126 zones

Immediate At-a-Glance Status

- 122 x 32 alphanumeric LCD display provides continuous information for the entire network

Automatic Datalogging Capability

- Controller provides automatic datalogging within cast aluminum enclosure
- Sensor concentrations and alarms is recorded for analysis

Easy Installation

- Cost is reduced by addressable RS-485 MODBUS communication protocol
- Installation requires only two pairs of wires to connect each gas sensors and relay modules to one of the controller's three input channels

Centralized Information

- Interface with or function individually with plant control

Applications

- Garage Ventilation Control
- IAQ Control
- Perimeter Monitoring
- Refrigerant Leak Detection Monitoring
- Zoned Valve Cut-off Control

Find out more

www.honeywellanalytics.com

Contact Honeywell Analytics:

USA, Central and South America

Honeywell Analytics, Inc.
23500 W. 105th Street, MD 400
Olathe, KS 66061
USA
Toll-free: 800.444.9935
Fax: 913.712.5580
Toll-free fax: 888.328.2417
detectgas@honeywell.com

Technical Services

ha.service@honeywell.com

www.honeywell.com

Canada

Honeywell Analytics
4006 Matte Blvd., Unit G
Brossard, QC, Canada
JAY 2P4
Toll-free: 800.563.2967
Tel: 450.619.2450
Fax: 888.967.9938
detectgas@honeywell.com

Europe and the rest of the world

Life Safety Distribution AG
Weiherallee 11a
CH-8610 Uster
Switzerland
Tel: +41 (0)44.943.4300
Fax: +41 (0)44.943.4398
gasdetection@honeywell.com

Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.



Tollfree in Western Canada: 1-888-388-1592
microwatt.com • mwsales@microwatt.com