

# Here's something to get **PUMPED** up about in portable gas detection.

## Introducing the **MGC Pump** with a 5 day continuous run on a single charge.



- ◆ **6 month calibration cycle**
- ◆ **Draw from up to 75 feet**
- ◆ **Low maintenance**
- ◆ **Stainless steel inlet**

### **A New Option in Portable Gas Detection**

Twice a day, every day... that's how often you have to charge most portable gas detectors, until now. Introducing the Multi Gas Clip Pump (MGC Pump) from Gas Clip Technologies, the only portable multi gas detector with an internal sampling pump that can go an entire work week without a charge.

### **A Long-Lasting Family Tradition**

The MGC Pump follows in the long line of portable gas detectors by Gas Clip Technologies that last and last and last. Being able to go a long time between charges is a family tradition.

### **The Secret to a Long Life**

Like our MGC, the MGC Pump uses low-power photometric technology to detect combustible gases (LEL) rather than age-old pellistor technology. The MGC Pump uses an IR source which conserves power and helps the battery last and last.

### **Ergonomic Design Makes for a Good Fit**

The MGC Pump is also designed for comfort. The reduced, sloping shape of the holding area at the bottom of the instrument makes the MGC Pump a comfortable fit in the hands of your workers. It is fully submersible and simple to operate. The MGC Pump offers a one button design and the largest LCD screen in the industry so it's easy to read.

### **Calibrate the MGC Pump Once Every 6 Months**

Other multi gas detectors require calibration anywhere from 1 to 3 months. The MGC Pump can go 6 months without being calibrated. This is an added benefit of IR sensing technology because IR is immune to pellistor sensor poisons such as silicone or H<sub>2</sub>S.

### **Call Today or Visit [GasClipTech.com](http://GasClipTech.com)**

Get pumped up today and call Gas Clip Technologies at **1.877.525.0808** or visit [gascliptech.com](http://gascliptech.com) to learn more about the MGC Pump. After all, time is money.



**Portable gas detectors you can count on.**

[www.gascliptech.com](http://www.gascliptech.com) ◆ Toll-free: 877.525.0808

# Specifications

## Included with the MGC Pump:

10' Sampling Hose  
10 Additional Filters; 5 Hydrophobic and 5 Particulate  
Stainless Steel Diffusion Stone



**GCT IR Link**



**MGC Pump Dock**

**Size** 5.7 x 3.0 x 1.5 in. (147 x 78 x 38.3 mm.)  
**Weight** 12.4 oz. (352g)  
**Temperature** -4° to +122°F (-20° to +50°C)  
**Humidity** 5% to 100% RH (non-condensing)  
**Battery Life** 5 days continuous  
 Pellistor: 30 hours continuous  
**Charge Time** 4 - 6 hours  
**Alarms** Visual, Vibrating, Audible (minimum 95 dB) Low, High, STEL, TWA and OL (Over Limit), Pump  
**LEDs** 4 red alarm bar LEDs  
 Yellow backlight (activated on button press)  
 Red backlight (activated on alarm condition)  
 Yellow Maintenance Notification LED  
**Display** Alphanumeric Liquid Crystal Display (LCD)  
**Logs** 25 Bump tests  
 25 Events  
 25 Calibrations  
 Continuous 1 second data logging (> 2 month typical capacity)  
**Tests** Full function self-test upon activation  
 Sensors, battery and circuitry conditions

**Ingress Protection** IP 67

**Gas Inlet** 1/8" barbed fitting

### Certifications and Approvals

**CSA:** Class1, Division 1, Group A, B, C and D  
 Class 1, Zone 0, AEx ia IIC T4 Ga  
 C22.2 No.'s 0, 152, 157  
 Ex ia IIC T4 Ga  
**IECEX:** IECEx CSA 14.0029  
 IEC 60079-0:2011, 60079-11:2011, 60079-26:2006  
**ATEX:** SIRA 14ATEX2120  
 CE II 1 G Ex ia IIC T4 Ga  
 EN 60079-0:2012, 60079-11:2012, 60079-26:2007  
 EN50270  
 ANSI/ISA S12.13.01  
**InMetro:** (pending)  
 UL-913  
 NCC xx-xxxxx Ex ia IIC T4 Ga (-20°C ≤ Ta ≤ 50°C)

**Pump Draw** Sample from up to 75 ft (23 m)

**Warranty** Full 2 years

**Gases**  
 H<sub>2</sub>S 0 - 100 PPM (0.1 PPM increments)  
 CO 0 - 500 PPM (1 PPM increments)  
 Combustible gas 0 - 100% LEL (0.1% LEL increments)  
 O<sub>2</sub> 0 - 30% vol. (0.1% vol. increments)

**Sensor Type** H<sub>2</sub>S, CO, O<sub>2</sub>: Single plug-in electrochemical cell  
 Combustible: Plug-in infrared (IR) or pellistor

### User Options

User message Maintenance notification  
 TWA/STEL intervals TWA method  
 Languages (6) Sensor enable/disable  
 Pump test SAFE display  
 Self-Test lock Dock lock  
 Auto-zero on start up Calibration gas  
 Bump test interval Calibration interval  
 Low/High alarm TWA/STEL alarm

Part #	Description
<b>MGC-IR-PUMP</b>	<b>4 Gas Monitor containing IR sensor and internal pump</b>
<b>MGC-P-PUMP</b>	<b>4 Gas Monitor containing Pellistor sensor and internal pump</b>
<b>MGC-DOCK-PUMP</b>	<b>4 bay calibration and bump test station</b>
<b>MGC-WMDOCK-PUMP</b>	<b>4 bay wall mounted calibration and bump test station</b>
<b>MGC-DOCK-HP-PUMP</b>	<b>MGC PUMP 4 Bay Hi-Pressure Dock Station</b>
<b>MGC-WMDOCK-HP-PUMP</b>	<b>MGC Pump 4 Bay Hi-Pressure Wall Mount Dock</b>
<b>GCT-IR-LINK</b>	<b>GCT IR communication module w/USB cable</b>
<i>Please contact Gas Clip Technologies for additional spares, accessories and gas.</i>	

Distributed By:



Tollfree in Western Canada: 1-888-388-1592  
microwatt.com • mwsales@microwatt.com



**Portable gas detectors you can count on.**

www.gascliptech.com ♦ Toll-free: 877.525.0808  
2010-2014© Gas Clip Technologies, Inc. All Rights Reserved.